



TIDAL WRAP MARINE PRIMER PASTE

PRODUCT DATA SHEET

Description Petrolatum based primer for application on metal surfaces prior to wrapping with Anti Corrosion Petro Tape UW.

Use For long-term corrosion protection of steel piles and structural steel in marine environments. The **PT Marine Tape** is designed for use either immersed or above the tidal zone applications.

Temperature: Withstands temperatures -46 Deg. C. to 70 Deg. C.
-50 Deg. F. to 158 Deg. F.

Color: Brown

Surface Preparation: Remove loose dirt and contaminants using a wire brush.
Eliminate all sharp edges and welding splatter.

Application: Petro Primer can be brushed or ragged on with a thin, uniform coat. Utilize heavier application on pitted areas, bolt heads, or any other contoured or sharp surface.

Packaging: One gallon pail x 4 per Box



TYPICAL PROPERTIES	TEST METHOD	DATA
Congealing Point	ASTM D398	57.3 ⁰ C
Flash Point	ASTM D92	100 ⁰ C
Specific Gravity at 25° C	ASTM D70	0.89
Coverage		2.5m ² /Kg
Temperature Range		5° to 45° C
<i>For Application</i>		
<i>For Service</i>		25° to 70° C
SURFACE PREPARATION	Surfaces must be scraped and brushed making sure there is no marine growth.	
PACKAGING	4Kg. Pails	